



BRICKFORM Color Selection Guide

Top Sellers



For Technical Assistance 1-800-483-9628

Federal Yellow

3100

Pool Blue*

660

- Antique Release Tinta' Seal
- Antique-It
- Color Hardener
 Overlay Colorants

 - Refresh



Made to Order



methods, jobsite conditions, texturing or finishing techniques such as brooming or troweling, the use of sealers, and slight color-drifts in raw materials are likely to produce variations of the colors. The sample chips represented on this color chart were produced to compare to concrete with a flat troweled finish, sealed with BRICKFORM solvent-based sealer.

*Brickform Overlay Colorants not available in Smokey Blue and Pool Blue NOTE: Tinta Seal and Refresh Color Packs are Made to Order only

Defining Decorative Concrete Since 1971

BRICKFORM.COM



Prior to using Brickform products, refer to the current TIS and SDS available at brickform.com or by using the QR codes below.

Color Hardener

Color Hardener is manufactured with the finest UV-resistantpigments and premium aggregates available. When properly applied and troweled into newly placed, fresh concrete, it forms a colored concrete surface that is resistant to weathering, wear, and normal abrasion.

- 90 to 120 ft² per 60 lb. bucket
- Improves abrasion resistance
- Hardens the concrete surface



Antique Release

AntiqueReleaseisahydrophobicpowderthatimparts colorwhileservingasabondbreakerforstamping. Itismadefromafinelygroundformulathatcreates beautifullyantiquedconcretesurfaces. Duringthe stampingprocess, Antique Releaseispressedinto the concretesurface, creatingase condary coloring effect once washed off and sealed.

- 800 to 1000 ft² per 30 lb. bucket
- · Bond breaker and Antiquing agent
- Fade-resistant



Antique-It

Antique-Itisawater-solubleantiquingagentdesigned toimpartasecondarycolorortohighlightstamped concreteortexturedoverlays. Antique-Itiseasyto apply, driesfast, and provides a durable colorthat closely resembles the look of antique release powder. Use Antique-Itonnewly placed hardened concreteor to rejuve nate old unsealed stamped concrete.

- 2000 to 3000 ft² per 3 lb. container
- Unlimited effects and color combinations
- Dust free application



Overlay Colorants

The Overlay Colorants are premeasured bottles of Liquid Integral Colorants designed to add color to the base cement of SM Professional Grade, SM Pro PLUS, Cem-Coat Plus and Stampable Overlay (SC-60, White Mix).

- 10 oz bottles
- Use 1 bottle per bag of Overlay
- 6 per case
- * Brickform Overlay Colorants not available in Smokey Blue and Pool Blue



Tinta' Seal

Enhanceand correct color with Tinta' Seal. Tinta' Seal mixes with Brick forms olvent-based sealers to add op a que color to integrally colored, stamped, and overlaid concrete surfaces. Each 16-ounce tint pack conveniently mixes in a 5-gallon pail of solvent-based sealer to create a tinted sealer.

- 16 oz. bottle
- 1 bottle per 5 gal. of sealer
- Color matching available
- Compatible with Gem-Seal, Poly-Seal, and Gem Cure & Seal
- NotrecommendedforusewithGem-GuardSB
- Made to Order Only



Distributed by:

Refresh

BrickformRefreshisasolvent-based,semi-opaque stain used to impart color on unsealed, porous concreteandmasonrysurfaces.Refreshisgreatfor correctingsurfacediscoloration,upgradingexisting concrete, or blending together multiple pours of integrallycoloredconcrete.Foraddedprotectionand colorenhancement,Refreshcanbesealed using spray-applied BrickformGem-Sealor Poly-Seal.

- 1000-1500 ft² per 5 gal pail
- UV resistant
- Apply with acetone resistant sprayer
- Made to Order Only



WARRANTY: These products are not intended for publicuse and are intended for use by licensed contractors and installers, experienced and trained in the use of these products. They are warranted to be of uniform quality, within manufacturing to lerances. The manufacturer has no control over the use of these products, therefore, no warranty, expressed or implied, is or can be made either as to the affects or results of such use. In any case, the manufacturer's obligations shall be limited to refunding the purchase price or replacing material provento be defective. The enduser shall be responsible for determining product's suitability and assumes all risks and liability. CAUTIONS+KEEPOUTOFREACHOFCHILDREN. Before using or handling, read the appropriate Technical Data Sheet, Safety Data Sheet and Warranty. DONOTTAKEINTERNALLY Avoid contact with skin and eyes. Use only with a NIOSHapproved respirator when using the seproducts. Installation guidelines available at brick form.com.



BRICKFORM®

A Division of Solomon Colors, Inc.
4050 Color Plant Road, Springfield, IL 62702
800-483-9628 • brickform.com
An Employee-Owned Company
©2024 Brickform. All rights reserved. Printed in U.S.A.

BF-COLORCHART 20240903